

WIRELESS GO II™

DUAL CHANNEL WIRELESS MICROPHONE SYSTEM



3.5mm, USB-C, iOS®
AUDIO OUTPUT*



BUILT-IN
MICROPHONE



DIGITAL
TRANSMISSION

The next generation of wireless audio from RØDE is here. Wireless GO II is an extremely versatile and ultra-compact dual channel wireless microphone system consisting of a single receiver and two transmitters. Featuring a high-quality microphone built into each transmitter for completely wireless operation, flexible outputs for connecting to cameras, computers and smartphones, extended transmission range and much more, Wireless GO II is the perfect microphone for a wide range of content creation applications.



- Dual channel wireless microphone system
- Series IV 2.4GHz digital transmission, 128-bit encryption
- 3.5mm TRS analog output, USB-C and iOS compatible digital audio output
- In-built rechargeable lithium-ion battery – up to 7 hours battery life
- Ability to switch between mono or stereo output
- 200m transmission range (line of sight)



ACOUSTIC & ELECTRICAL SPECIFICATIONS


Acoustic Principle:	Pre-polarised pressure transducer
Polar Pattern:	Omnidirectional
Frequency Range:	50Hz – 20kHz
Maximum SPL (Mic):	100 dB SPL (1kHz @ 1m) dBu
Maximum Input Level (3.5mm):	-20dBV
Microphone Preamp Gain:	20dB
Equivalent Noise Level (A-Weighted):	22dBA
Power Requirements:	In-built rechargeable lithium-ion battery charged via USB 5V, 0.3A
Operating Time:	Up to 7 hours
Analog Inputs:	3.5mm TRS (lavalier microphone input)
Analog Outputs:	3.5mm TRS
Transmission Range:	200m (line of sight)
Computer Connectivity:	USB Type-C
Operating System Requirements:	macOS 10.11 above Windows 10 and above

MECHANICAL SPECIFICATIONS


Weight (grams):	TX: 30g RX: 32g	
Dimensions (millimetres):	TX Length: 44 Width: 45.3 Height: 18.3	RX Length: 44 Width: 45.5 Height: 18.3
Included Accessories:	3 x SC20 1 x SC5 3 x Furry 1 x Pouch Bag	

RX


Top view



Bottom view




Profile




TX


Top view




Bottom view



Profile



POLAR PATTERN



FREQUENCY RESPONSE

